



54000BS 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic BS

Document version: 16 Jul 2024



Description

MPM 4-Stroke Motorcycle Oil 10W-40 Semi Synthetic is suitable for air and water-cooled 4-stroke engines and transmissions. This motor oil provides high quality protection. The multigrade SAE 10W-40 motor oil is designed for motorcycles with dry and wet plate clutches.

Application manual

According to the specifications of

API SL
JASO MA / MA2

Packaging units

ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
54001BS	1 L	6	450
P54000BS	1 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.855	kg/l	ASTM D4052
Colour	Brown		
SAE	10W-40		
Kinematic Viscosity at 40°C	88.0	mm ² /s	ASTM D445
Kinematic Viscosity at 100°C	13.8	mm ² /s	ASTM D445
Viscosity Index	162		ASTM D2270
Flashpoint	201	°C	ASTM D92
Pourpoint	-36	°C	ASTM D97
Total Base Number	9.1	mgKOH/g	ASTM D2896

These characteristics are typical of current production. Variations in these characteristics may occur.